Secoroc Rotary Products

Dirt Digger PDC Bits

6-3/4" DP316

Adding value through performance

Applications:

- Cost effective PDC drill bit ideally suited for mining, construction, fiber optic, water well, geothermal and shallow oil & gas drilling
- Tapered parabolic profile design offers an optimal combination of cutter protection and ROP capabilities for a variety of formations and drilling conditions
- PDC bit advantages over a traditional roller cone bit include longer bit life, smoother drilling operations and increased penetration rates

Design Features:

- 3D designed one-piece 4140 alloy steel body is CNC machined to exact design specifications for maximum blade and body strength
- Optimized cutter distribution profile for blade count, cutter quantity, drilling conditions and bit stability
- Force-balanced PDC cutter locations minimize bit whirl and drill a precise round hole
- Asymmetrical blade layout reduces drilling harmonics
- Dirt Digger Premium (DP) bits have Tungsten Carbide Hardface applied to critical areas of the bit for erosion resistance





14 @ 16 mm PDC

Product Specifications:

General Data:

- Body Type One-piece Steel Cutting Structure: - Gage Length 1.375 in / 34.925 mm - Face Cutters

- Overall Length 10.92 in / 277.35 mm - Back-Up Cutters N/A

- Shipping Weight **TBD** - Gage Cutters 3 @ 13 mm PDC

- Product Number

91002877

Hydraulics:

- Nozzle Type Connection: 6 @ 16/32" Ports

1.18 in² - Pin Connection 3-1/2" API Reg Pin - TFA

- Fishneck Diameter 4.75 in / 120.65 mm

- Fishneck Length 3.00 in / 76.20 mm **Recommended Operating Parameters:**

- Make-Up Length 7.23 in / 183.68 mm - Weight on Bit (WOB) 3,000-15,000 lbs - Make-Up Torque - Rotary Speed (RPM) 60-150 RPM 6,300-8,400 ft-lbs

Atlas Copco Secoroc LLC 6146 South 350 West, Salt Lake City, UT 84107 USA Phone: +1 801 281 1682

E-mail: secoroc@se.atlascopco.com www.atlascopco.com/us/

